# HID PROXCARD II CLAMSHELL CARD

# 125 kHz HID Proximity Credentials





HID ProxCard II proximity access card is the industry choice for a cost-effective solution to proximity access control, with universal compatibility with all HID Proximity Readers. The ProxCard II provides durable packaging and consistent read range.

## Feature List:

- \* Price competitive with all other card technologies.
- \* Offers universal compatibility with all HID proximity readers.
- \* Provides durable packaging and consistent read range.
- \* Provides an external number for easy identification and control.
- \* Supports formats up to 85 bits, with over 137 billion codes.
- \* Custom pre-printed artwork available.
- \* A PVC overlay allows for on-site photo ID using most direct image printers.
- \* Thin enough to carry in a wallet or purse.
- \* Create Photo ID card with model 1324 Printable Adhesive Label
- \* Proven, Reliable Technology: Offers extremely consistent read range. Unaffected by body shielding or variable environmental conditions, even when close to keys and coins.
- \* Convenient to Use: Can fit into a wallet or purse. Use with a strap and clip as a photo ID badge.
- \* Cross-reference: A cross-reference list correlating the external card number and the programmed ID number is provided for easy system administration.
- \* Security: Offers over 137 billion unique codes.
- \* Long Life: Passive, no-battery design allows for an infinite number of reads.
- \* Durability: Strong, flexible and resistant to cracking and breaking.

### **Technical Specifications:**

|                                  |                                |                             |                            | 0.075"    |
|----------------------------------|--------------------------------|-----------------------------|----------------------------|-----------|
| Dimensions                       | 2.135" x 3.385" x 0.075" MAX.  |                             | 2.135"                     | (0.19 cm) |
| Weight                           | 0.24 oz. (6.8 gm)              |                             | (5.4 cm) ► MAX.            | MAX.      |
| Weight                           | 0.24 02. (0.0 gm)              |                             | MAA.                       |           |
| Operating Temperature            | -50° to 160° F (-45° to 70° C) |                             |                            |           |
| Read Range                       |                                |                             |                            |           |
| ProxPoint Plus Reader            | Up To 3" (7.5 cm)              | AMITEL                      |                            |           |
| MiniProx Reader                  | Up To 5.5" (14 cm)             |                             |                            | 3.385"    |
| ThinLine II Reader               | Up To 5.5" (14 cm)             |                             |                            | (8.6 cm)  |
| ProxPro Reader                   | Up To 8" (20 cm)               |                             |                            |           |
| ProxPro II Reader                | Up To 9"(22.9 cm)              | ProxCard® II                |                            |           |
| MaxiProx Reader                  | Up To 24" (60 cm)              | ProxCard II Artwork (front) | All dimensions are nominal | <u> </u>  |
| * Demonstrations to and in stall |                                |                             |                            |           |

\* Dependent on local installation conditions.

### How To Order Credentials:

| Base | Product | Credential                               | Facility Code  | Credential   | Bit   |
|------|---------|--|--|--|---|
| Part | Make    | Type                                     | & Start ID   | Numbering  | Format  |
| 224  | HID     | <b>C</b> - ProxCard II<br>Clamshell Card | C - Current Facility<br>Code & Start ID<br>S - Special Facility<br>Code & Start ID | H - Sequential<br>Matching Internal/<br>External Numbers | <b>30</b> - Secure AMTEL<br>Format 30 Bit<br><b>26</b> - Generic HID<br>Format 26 Bit |

10773 NW 58th Street # 334, Doral, FL 33178 Phone: (305) 597-5000 | Fax: (305) 402-0254 Website: www.amtelasps.com

